

# pigPRO™



US PATENT# 5,263,220

1575 - 90 Ave Edmonton, AB Canada T6P 0E2

Ph: 780.416.4850 | Fax: 780.416.4829 | [apachepipe.com](http://apachepipe.com) | Email: [sales@apachepipe.com](mailto:sales@apachepipe.com)

8-1

*world class world wide*

# p i g P R O™

## SERIES 53

Visual/Electrical Indication

Manual/Auto Reset



### Features:

Base Model 53-0000 is a combined visual/electrical indicator with manual/automatic reset. It includes a thread mounting nipple, standard lower housing with fluorocarbon ORings, hemispherical plunger with a flag assembly and weather sealed & explosion proof limit switch. The switch employed on this model is NEMA rated, UL listed and CSA certified to suit most applications.

### Options:

Flange Mount - Flange base models are manufactured to mount to existing flanged connections and are available in class 150, 300, 600 or 900 ANSI flanges. Conversions kits are also available which enable installation onto the mountings of other manufacturers.

### Extension Pole:

Aluminum extensions can be attached to enable detection of the pigs passage on buried pipelines. All pressure sealing components remain below the extension module. Available in lengths 2' to 8'.

1575 - 90 Ave Edmonton, AB Canada T6P 0E2

8-2

Ph: 780.416.4850 | Fax: 780.416.4829 | [apachepipe.com](http://apachepipe.com) | Email: [sales@apachepipe.com](mailto:sales@apachepipe.com)

*world class world wide*

# pigPRO™

## SERIES 55

Electrical Indication

Auto Reset



### Features:

Base Model 55-0000 is an electrical indicator with automatic reset. It includes a thread mounting nipple, standard lower housing with fluorocarbon O-Rings, hemispherical plunger and weather sealed & explosion proof limit switch. The switch employed on this model is NEMA rated, UL listed and CSA certified to suit most applications.

### Options:

Flange Mount -Flange base models are manufactured to mount to existing flanged connections and are available in class 150, 300, 600 or 900 ANSI flanges. Conversions kits are also available which enable installation onto the mountings of other manufacturers.

### Extension Pole:

Aluminum extensions can be attached to enable detection of the pigs passage on buried pipelines. All pressure sealing components remain below the extension module. Available in lengths 2' to 8'.

# p i g P R O™

## SERIES 57

Visual Indication

Manual Reset



### Features:

Our most popular pigPRO™ the base Model 57-0000 is a visual flag indicator with manual reset. It includes a thread mounting nipple, standard lower housing with fluorocarbon O-Rings, hemispherical plunger with a flag assembly.

### Options:

Flange Mount -Flange base models are manufactured to mount to existing flanged connections and are available in class 150, 300, 600 or 900 ANSI flanges. Conversions kits are also available which enable installation onto the mountings of other manufacturers.

### Extension Pole:

Aluminum extensions can be attached to enable detection of the pigs passage on buried pipelines. All pressure sealing components remain below the extension module. Available in lengths 2' to 8'.

1575 - 90 Ave Edmonton, AB Canada T6P 0E2

8-4

Ph: 780.416.4850 | Fax: 780.416.4829 | [apachepipe.com](http://apachepipe.com) | Email: [sales@apachepipe.com](mailto:sales@apachepipe.com)

*world class world wide*